





修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2020-08-04




Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2x4P	3.00	7.00	4.35	2x20P	19.00	23.00	20.35
2x5P	4.00	8.00	5.35	2x25P	24.00	28.00	25.35
2x6P	5.00	9.00	6.35				
2x7P	6.00	10.00	7.35				
2x8P	7.00	11.00	8.35				
2x9P	8.00	12.00	9.35				
2x10P	9.00	13.00	10.35				
2x11P	10.00	14.00	11.35				
2x12P	11.00	15.00	12.35				
2x15P	14.00	18.00	15.35				

SPECIFICATIONS:

Current Rating: 1A AC,DC
Voltage Rating: 50V AC,DC
Temperature Range: -25°C ~ +85°C
Contact Resistance: 20MΩ Max.
Insulation Resistance: 100MΩ Min.
Withstanding Voltage: 500V AC/minute
Material: Nylon 66,UL94V-0 (White)

				深圳市华德共创科技有限公司 Shenzhen Huade co-create Technology Co.,LTD TEL : 0755-27129737 FAX : 0755-29940187							
-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表						TITLE: 产品名称：1.00mm Pitch Housing					
X.X	±0.30	X.X°	±3°	APPD: 核准:	XIE	PART NO:		HDGC1002H-2xXP			
X.XX	±0.30	X.XX°	±2°	CHECK: 校对:	WANG	DATE	SCALE	UNIT	CODE NUMBER		
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图:	WANG	2020-08-04	6:1	mm	A001		