






修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2020-04-12



Ordering Information & Dimensions

Circuits	Dimensions(mm)				
	A	B	C	D	E
2x2P	1.00	5.00	1.82	3.46	4.06
2x3P	2.00	6.00	2.82	4.46	5.06
2x4P	3.00	7.00	3.82	5.46	6.06
2x5P	4.00	8.00	4.82	6.46	7.06
2x6P	5.00	9.00	5.82	7.46	8.06
2x7P	6.00	10.00	6.82	8.46	9.06
2x8P	7.00	11.00	7.82	9.46	10.06
2x9P	8.00	12.00	8.82	10.46	11.06
2x10P	9.00	13.00	9.82	11.46	12.06
2x11P	10.00	14.00	10.82	12.46	13.06
2x12P	11.00	15.00	11.82	13.46	14.06
2x13P	12.00	16.00	12.82	14.46	15.06
2x14P	13.00	17.00	13.82	15.46	16.06
2x15P	14.00	18.00	14.82	16.46	17.06
2x16P	15.00	19.00	15.82	17.46	18.06
2x17P	16.00	20.00	16.82	18.46	19.06
2x18P	17.00	21.00	17.82	19.46	20.06
2x19P	18.00	22.00	18.82	20.46	21.06
2x20P	19.00	23.00	19.82	21.46	22.06

SPECIFICATIONS:

Current Rating: 1A AC,DC

Voltage Rating: 50V AC,DC

Temperature Range: -25°C ~ +85°C

Contact Resistance: 40mΩ Max.

Insulation Resistance: 100MΩ Min.

Withstanding Voltage: 500V AC/minute

Pin Material: Phosphor Bronze/Tin over Nickel

Material: LCP UL94V-0(Natural)

深圳市华德共创科技有限公司
Shenzhen Huade co-create Technology Co.,LTD
TEL : 0755-27129737 FAX : 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表					TITLE: 产品名称: 1.00mm Pitch 90° Wafer			
X.X	±0.30	X.X°	±3°	APPD: 核准:	XIE			
X.XX	±0.30	X.XX°	±2°	CHECK: 校对:	WANG			
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图:	WANG			
PART NO: 产品编号:					HDGC1006WR-S-2xXP			
DATE					SCALE	UNIT	CODE NUMBER	
2020-04-12					1:1	mm	A003	