




修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2013-05-07



Ordering Information & Dimensions:

PART NO.	Dimensions	
	A	B
2P	1.25	4.40
3P	2.50	5.65
4P	3.75	6.90
5P	5.00	8.15
6P	6.25	9.40
7P	7.50	10.65
8P	8.75	11.90
9P	10.00	13.15
10P	11.25	14.40
11P	12.50	15.65
12P	13.75	16.90
13P	15.00	18.15
14P	16.25	19.40
15P	17.50	20.65
20P	23.75	26.90
25P	30.00	33.15
30P	36.25	39.40

Unit: mm

SPECIFICATIONS:

Current Rating: 1A AC,DC
Voltage Rating: 150V AC,DC
Temperature Range: -25°C ~ +85°C
Contact Resistance: 30mΩ Max.
Insulation Resistance: 500MΩ Min.
Withstanding Voltage: 500V AC/minute
Material: Nylon 66,UL94V-0(White)



深圳市华德共创科技有限公司

Shenzhen Huade co-create Technology Co.,LTD

TEL : 0755-27129737 FAX : 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表						TITLE: 产品名称: 1.25mm Pitch Housing			
X.X	±0.30	X.X°	±3°	APPD: 核准:	XIE	PART NO: 产品编号: HDGC1255HA-XP			
X.XX	±0.30	X.XX°	±2°	CHECK: 校对:	WANG	DATE	SCALE	UNIT	CODE NUMBER
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图:	WANG	2013-05-07	1:1	mm	A001