





修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2017-01-10



Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
4P	3.81	7.59	16P	19.05	22.83
6P	6.35	10.13	18P	21.59	25.37
8P	8.89	12.67	20P	24.13	27.91
10P	11.43	15.21	22P	26.67	30.45
12P	13.97	17.75	24P	29.21	32.99
14P	16.51	20.29	26P	31.75	35.53

SPECIFICATIONS:

Current Rating: 1.2A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range:-25°C~+85°C

Contact Resistance: 20mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage:500V AC/minute

Housing Material: PBT,UL94V-0(White)

Terminal Material: Phosphor Bronze/Tin over Nickel



深圳市华德共创科技有限公司

Shenzhen Huade co-create Technology Co.,LTD

TEL : 0755-27129737 FAX : 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表						TITLE: 产品名称：1.27mm Pitch Housing			
X.X	±0.30	X.X°	±3°	APPD: 核准：	XIE	PART NO: 产品编号：HDGC1272H-XP			
X.XX	±0.30	X.XX°	±2°	CHECK: 校对：	WANG	DATE	SCALE	UNIT	CODE NUMBER
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图：	WANG	2017-01-10	5:1	mm	A008