



修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2017-03-25



Ordering Information & Dimensions

Circuits	Dim(mm)		Circuits	Dim(mm)		Circuits	Dim(mm)	
	A	B		A	B		A	B
2x5P	5.08	7.54	2x21P	25.40	27.86	2x37P	45.72	48.18
2x6P	6.35	8.81	2x22P	26.67	29.13	2x38P	46.99	49.45
2x7P	7.62	10.08	2x23P	27.94	30.40	2x39P	48.26	50.72
2x8P	8.89	11.35	2x24P	29.21	31.67	2x40P	49.53	51.99
2x9P	10.16	12.62	2x25P	30.48	32.94	2x41P	50.80	53.26
2x10P	11.43	13.89	2x26P	31.75	34.21	2x42P	52.07	54.53
2x11P	12.70	15.16	2x27P	33.02	35.48	2x43P	53.34	55.80
2x12P	13.97	16.43	2x28P	34.29	36.75	2x44P	54.61	57.07
2x13P	15.24	17.70	2x29P	35.56	38.02	2x45P	55.88	58.34
2x14P	16.51	18.97	2x30P	36.83	39.29	2x46P	57.15	59.61
2x15P	17.78	20.24	2x31P	38.10	40.56	2x47P	58.42	60.88
2x16P	19.05	21.51	2x32P	39.37	41.83	2x48P	59.69	62.15
2x17P	20.32	22.78	2x33P	40.64	43.10	2x49P	60.96	63.42
2x18P	21.59	24.05	2x34P	41.91	44.37	2x50P	62.23	64.69
2x19P	22.86	25.32	2x35P	43.18	45.64			
2x20P	24.13	26.59	2x36P	44.45	46.91			

SPECIFICATIONS:

Current Rating: 1.5A AC,DC
Voltage Rating: 30V AC,DC
Temperature Range: -25°C ~ +85°C
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 500V AC/minute
Material: Polyester, UL94V-0(Black)

				深圳市华德共创科技有限公司			
Shenzhen Huade co-create Technology Co.,LTD				TEL : 0755-27129737 FAX : 0755-29940187			
-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表					TITLE: 产品名称: 1.27mm Pitch Housing		
X.X	±0.30	X.X°	±3°	APPD: 核准: XIE	PART NO: 产品编号: HDGC1275H-2xXP		
X.XX	±0.30	X.XX°	±2°	CHECK: 校对: WANG	DATE	SCALE	UNIT
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图: WANG	2017-03-25	3:1	mm
				CODE NUMBER A008			