





修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2017-03-25



P.C.B LAYOUT



Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2x5P	5.08	9.65	7.65	2x21P	25.40	29.97	27.97
2x6P	6.35	10.92	8.92	2x22P	26.67	31.24	29.24
2x7P	7.62	12.19	10.19	2x23P	27.94	32.51	30.51
2x8P	8.89	13.46	11.46	2x24P	29.21	33.78	31.78
2x9P	10.16	14.73	12.73	2x25P	30.48	35.05	33.05
2x10P	11.43	16.00	14.00	2x26P	31.75	36.32	34.32
2x11P	12.70	17.27	15.27	2x27P	33.02	37.59	35.59
2x12P	13.97	18.54	16.54	2x28P	34.29	38.86	36.86
2x13P	15.24	19.81	17.81	2x29P	35.56	40.13	38.13
2x14P	16.51	21.08	19.08	2x30P	36.83	41.40	39.40
2x15P	17.78	22.35	20.35	2x31P	38.10	42.67	40.67
2x16P	19.05	23.62	21.62	2x32P	39.37	43.94	41.94
2x17P	20.32	24.89	22.89	2x33P	40.64	45.21	43.21
2x18P	21.59	26.16	24.16	2x34P	41.91	46.48	44.48
2x19P	22.86	27.43	25.43	2x35P	43.18	47.75	45.75
2x20P	24.13	28.70	26.70	2x36P	44.45	49.02	47.02

SPECIFICATIONS:

Current Rating: 1.5A AC,DC
Voltage Rating: 30V AC,DC
Temperature Range: -25°C ~ +85°C
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 500V AC/minute
Pin Material: Phosphor Bronze/Gold over Nickel
Material: Nylon 9T, UL94V-0(Black)
Soldering Temperature: 260°C±5°C
Immersion Period: 3~5 seconds



深圳市华德共创科技有限公司

Shenzhen Huade co-create Technology Co.,LTD

TEL : 0755-27129737 FAX : 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表						TITLE: 1.27mm Pitch 产品名称: 90° Wafer			
X.X	±0.30	X.X°	±3°	APPD: 核准:	XIE	PART NO: HDGC1275WR-2xXP 产品编号:			
X.XX	±0.30	X.XX°	±2°	CHECK: 校对:	WANG	DATE	SCALE	UNIT	CODE NUMBER
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图:	WANG	2017-03-25	2.5:1	mm	A008