






修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2014-09-17



Ordering Information & Dimensions

Circuits	Dimensions(mm)				Circuits	Dimensions(mm)			
	A	B	C	D		A	B	C	D
2P	1.50	6.95	5.95	5.55	8P	10.50	15.95	14.95	14.55
3P	3.00	8.45	7.45	7.05	9P	12.00	17.45	16.45	16.05
4P	4.50	9.95	8.95	8.55	10P	13.50	18.95	17.95	17.55
5P	6.00	11.45	10.45	10.05	11P	15.00	20.45	19.45	19.05
6P	7.50	12.95	11.95	11.55	12P	16.50	21.95	20.95	20.55
7P	9.00	14.45	13.45	13.05					

SPECIFICATIONS:

Current Rating: 2A AC,DC
Voltage Rating: 150V AC,DC
Temperature Range: -25°C ~ +85°C
Contact Resistance: 20mΩ Max.
Insulation Resistance: 1000MΩ Min.
Withstanding Voltage: 500V AC/minute
Material: Nylon 66,UL94V-0(Black)



深圳市华德共创科技有限公司

Shenzhen Huade co-create Technology Co.,LTD
TEL : 0755-27129737 FAX : 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表						TITLE: 产品名称：1.50mm Pitch Housing			
X.X	±0.30	X.X°	±3°	APPD: 核准：	XIE	PART NO: 产品编号：HDGC1501HB-XP			
X.XX	±0.30	X.XX°	±2°	CHECK: 校对：	WANG	DATE	SCALE	UNIT	CODE NUMBE
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图：	WANG	2014-09-17	5:1	mm	A008