

修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2012-10-23

技术指标:

1. 温度范围: $-25^{\circ}\text{C}\sim 85^{\circ}\text{C}$.
2. 额定电压: 250V AC, DC.
3. 耐电压: 500V AC/minute.
4. 接触电阻: $\leq 20\text{m}\Omega$.
5. 绝缘电阻: $\geq 1000\text{M}\Omega$.
6. 额定电流: 2.5A AC, DC.

CKT	A	B	C	D	E
2P	1.50	3.60	4.10	1.20	3.00
3P	3.00	5.10	5.60		
4P	4.50	6.60	7.10	2.50	4.30
5P	6.00	8.10	8.60		
6P	7.50	9.60	10.10		
7P	9.00	11.10	11.60	4.50	6.80
8P	10.50	12.60	13.10		
9P	12.00	14.10	14.60		
10P	13.50	15.60	16.10		
11P	15.00	17.10	17.60		
12P	16.50	18.60	19.10		
13P	18.00	20.10	20.60		
14P	19.50	21.60	22.10		
15P	21.00	23.10	23.60		
16P	22.50	24.60	25.10		

HDGC 深圳市华德共创科技有限公司
Shenzhen Huade co-create Technology Co.,LTD
TEL : 0755-27129737 FAX : 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表					TITLE: 产品名称：1.50mm Pitch Housing				
X.X	±0.30	X.X°	±3°	APPD: 核准:	XIE	PART NO: 产品编号：HDGC1502HA-XP-2			
X.XX	±0.30	X.XX°	±2°	CHECK: 校对:	WANG	DATE	SCALE	UNIT	CODE NUMBER
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图:	WANG	2012-10-23	6:1	mm	A003