


修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2023-10-25



SPECIFICATIONS:

Current Rating: 2A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$

Contact Resistance: 20m Ω Max.

Insulation Resistance: 500M Ω Min.

Withstanding Voltage: 500V AC/minute

Material: PA66 , UL94V-0(Natural)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			
	A	B	C	D
2P	1.50	6.30	2.50	1.50
3P	3.00	7.80	4.00	1.50
4P	4.50	9.30	5.50	1.50
5P	6.00	10.80	4.50	3.00
6P	7.50	12.30	6.00	3.00
7P	9.00	13.80	7.50	6.00
8P	10.50	15.30	9.00	6.00
9P	12.00	16.80	10.50	7.50
10P	13.50	18.30	12.00	7.50
11P	15.00	19.80	13.50	7.50
12P	16.50	21.30	15.00	7.50
13P	18.00	22.80	16.50	7.50
14P	19.50	24.30	18.00	7.50
15P	21.00	25.80	19.50	7.50



深圳市华德共创科技有限公司

Shenzhen Huade co-create Technology Co.,LTD

TEL : 0755-27129737

FAX : 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表					TITLE: 产品名称：1.50mm Pitch Housing			
X.X	±0.30	X.X°	±3°	APPD: 核准：XIE	PART NO: 产品编号：HDGC1508HM-XP			
X.XX	±0.30	X.XX°	±2°	CHECK: 校对：WANG	DATE	SCALE	UNIT	CODE NUMBE
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图：WANG	2023-10-25	1:1	mm	A001