



修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNA TURE	日期 DATE
A0		NEW RELEEASE	WANG	2017-11-22





P C B LAYOUT





SPECIFICATIONS:

Current Rating: 2A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range:-25°C ~ +85°C
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 500V AC/minute
Pin Material: Brass/Gold over Nickel
Material: Nylon 6T,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dim(mm)	
	A	B
2x2P	2.00	4.50
2x3P	4.00	6.50
2x4P	6.00	8.50
2x5P	8.00	10.50
2x6P	10.00	12.50
2x7P	12.00	14.50
2x8P	14.00	16.50
2x9P	16.00	18.50
2x10P	18.00	20.50
2x11P	20.00	22.50
2x12P	22.00	24.50
2x13P	24.00	26.50
2x14P	26.00	28.50

Circuits	Dim(mm)	
	A	B
2x15P	28.00	50.50
2x16P	30.00	32.50
2x17P	32.00	34.50
2x18P	34.00	36.50
2x19P	36.00	38.50
2x20P	38.00	40.50
2x21P	40.00	42.50
2x22P	42.00	44.50
2x23P	44.00	46.50
2x24P	46.00	48.50
2x25P	48.00	50.50
2x26P	50.00	52.50
2x27P	52.00	54.50

Circuits	Dim(mm)	
	A	B
2x28P	54.00	56.50
2x29P	56.00	58.50
2x30P	58.00	60.50
2x31P	60.00	62.50
2x32P	62.00	64.50
2x33P	64.00	66.50
2x34P	66.00	68.50
2x35P	68.00	70.50
2x36P	70.00	72.50
2x37P	72.00	74.50
2x38P	74.00	76.50
2x39P	76.00	78.50
2x40P	78.00	80.50

深圳市华德共创科技有限公司
Shenzhen Huade co-create Technology Co.,LTD
TEL：0755-27129737 FAX：0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表						TITLE: 产品名称：	2.00mm Pitch 180 ° Female Header		
X.X	±0.30	X.X°	±3°	APPD: 核准：	XIE	PART NO: 产品编号：	HDGC2005HWV-S-F-2xXP-Y		
X.XX	±0.30	X.XX°	±2°	CHECK: 校对：	WANG	DATE	SCALE	UNIT	CODE NUMBER
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图：	WANG	2017-11-22	5:1	mm	A008