





修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2012-03-10



Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2x2P	2.00	8.00	2x14P	26.00	32.00
2x3P	4.00	10.00	2x15P	28.00	34.00
2x4P	6.00	12.00	2x16P	30.00	36.00
2x5P	8.00	14.00	2x17P	32.00	38.00
2x6P	10.00	16.00	2x18P	34.00	40.00
2x7P	12.00	18.00	2x19P	36.00	42.00
2x8P	14.00	20.00	2x20P	38.00	44.00
2x9P	16.00	22.00	2x21P	40.00	46.00
2x10P	18.00	24.00	2x22P	42.00	48.00
2x11P	20.00	26.00	2x23P	44.00	50.00
2x12P	22.00	28.00	2x24P	46.00	52.00
2x13P	24.00	30.00	2x25P	48.00	54.00

SPECIFICATIONS:
Current Rating: 3A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range:-25°C ~ +85°C
Contact Resistance: 10mΩ Max.
Insulation Resistance: 1000MΩ Min.
Withstanding Voltage: 800V AC/minute
Pin Material: Brass/Tin over Nickel
Material: Nylon 66,UL94V-0(Gray)

		深圳市华德共创科技有限公司			
		Shenzhen Huade co-create Technology Co.,LTD			
		TEL : 0755-27129737 FAX : 0755-29940187			
-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表			TITLE: 2.00mm Pitch 产品名称: 90° Wafer		
X.X	±0.30	X.X°	±3°	APPD: 核准:	XIE
X.XX	±0.30	X.XX°	±2°	CHECK: 校对:	WANG
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图:	WANG
		PART NO: 产品编号:		DATE	SCALE
		HDGC2006WRA-2xXP		2012-03-10	4:1
		UNIT		mm	CODE NUMBER
					A008