




A B C D E F

修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2023-10-07



Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2x2P	2.00	4.70	3.10	2x12P	22.00	24.70	16.30
2x3P	4.00	6.70	3.10	2x13P	24.00	26.70	16.30
2x4P	6.00	8.70	5.20	2x14P	26.00	28.70	16.30
2x5P	8.00	10.70	5.20	2x15P	28.00	30.70	16.30
2x6P	10.00	12.70	5.20	2x16P	30.00	32.70	16.30
2x7P	12.00	14.70	8.35	2x17P	32.00	34.70	16.30
2x8P	14.00	16.70	8.35	2x18P	34.00	36.70	16.30
2x9P	16.00	18.70	11.20	2x19P	36.00	38.70	16.30
2x10P	18.00	20.70	14.00	2x20P	38.00	40.70	16.30
2x11P	20.00	22.70	11.20				

SPECIFICATIONS:
Current Rating: 3A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -25°C ~ +85°C
Contact Resistance: 30mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1000V AC/minute
Material: Nylon 66,UL94V-0 (White)



深圳市华德共创科技有限公司

Shenzhen Huade co-create Technology Co.,LTD
TEL : 0755-27129737 FAX : 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表				TITLE: 产品名称: 2.00mm Pitch Housing	
X.X	±0.30	X.X°	±3°	APPD: 核准:	XIE
X.XX	±0.30	X.XX°	±2°	CHECK: 校对:	WANG
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图:	WANG
				PART NO: 产品编号:	HDGC2008H-2xXP
				DATE	SCALE
				UNIT	CODE NUMBER
				2023-10-07	1:1 mm A001