






修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2012-05-07



Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2P	2.00	4.60	2.30	10P	18.00	20.60	14.50
3P	4.00	6.60	2.30	11P	20.00	22.60	14.50
4P	6.00	8.60	4.30	12P	22.00	24.60	14.50
5P	8.00	10.60	6.50	13P	24.00	26.60	14.50
6P	10.00	12.60	6.50	14P	26.00	28.60	14.50
7P	12.00	14.60	6.50	15P	28.00	30.60	14.50
8P	14.00	16.60	6.50	16P	30.00	32.60	14.50
9P	16.00	18.60	6.50				

SPECIFICATIONS:

Current Rating: 3A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range:-25°C ~ +85°C
Contact Resistance: 30mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1000V AC/minute
Material: Nylon 66,UL94V-0 (White)



深圳市华德共创科技有限公司

Shenzhen Huade co-create Technology Co.,LTD

TEL : 0755-27129737 FAX : 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表				TITLE: 产品名称: 2.00mm Pitch Housing	
X.X	±0.30	X.X°	±3°	APPD: 核准:	XIE
X.XX	±0.30	X.XX°	±2°	CHECK: 校对:	WANG
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图:	WANG
				PART NO: 产品编号:	HDGC2008H-XP
				DATE	SCALE
				UNIT	CODE NUMBER
				2012-05-07	4:1 mm A001