


修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2013-02-12



Ordering Information:




HDGC2503H-XP - **
1 2

1.Part No.

2.Color

(blank) :Ivory

WH :White



Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	2.50	7.00	12P	27.50	32.00
3P	5.00	9.50	13P	30.00	34.50
4P	7.50	12.00	14P	32.50	37.00
5P	10.00	14.50	15P	35.00	39.50
6P	12.50	17.00	16P	37.50	42.00
7P	15.00	19.50	17P	40.00	44.50
8P	17.50	22.00	18P	42.50	47.00
9P	20.00	24.50	19P	45.00	49.50
10P	22.50	27.00	20P	47.50	52.00
11P	25.00	29.50			

SPECIFICATIONS:

Current Rating: 3A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -25°C ~ +85°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 800V AC/minute

Material: Nylon 66,UL94V-0(Ivory)



深圳市华德共创科技有限公司

Shenzhen Huade co-create Technology Co.,LTD

TEL : 0755-27129737 FAX : 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表				TITLE: 产品名称: 2.50mm Pitch Housing	
X.X	±0.30	X.X°	±3°	APPD: 核准:	XIE
X.XX	±0.30	X.XX°	±2°	CHECK: 校对:	WANG
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图:	WANG
				PART NO: 产品编号:	HDGC2503H-XP
				DATE	SCALE
				UNIT	CODE NUMBER
				2013-02-12	5:1
				mm	A008