







修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2015-04-25



Ordering Information:
HDGC2509HM-XP - **
1 2

1.Part No.
2.Color:
(blank):White
BK:Black



SPECIFICATIONS:
Current Rating: 3A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -25°C ~ +85°C
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage:1000VAC/minute
Material: Nylon 66,UL94V-0(White)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2P	2.50	8.70	5.90	9P	20.00	26.20	23.40
3P	5.00	11.20	8.40	10P	22.50	28.70	25.90
4P	7.50	13.70	10.90	11P	25.00	31.20	28.40
5P	10.00	16.20	13.40	12P	27.50	33.70	30.90
6P	12.50	18.70	15.90	13P	30.00	36.20	33.40
7P	15.00	21.20	18.40	14P	32.50	38.70	35.90
8P	17.50	23.70	20.90	15P	35.00	41.20	38.40



深圳市华德共创科技有限公司

Shenzhen Huade co-create Technology Co.,LTD

TEL : 0755-27129737 FAX : 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表				TITLE: 产品名称: 2.50mm Pitch Housing	
X.X	±0.30	X.X°	±3°	APPD: 核准:	XIE
X.XX	±0.30	X.XX°	±2°	CHECK: 校对:	WANG
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图:	WANG
				PART NO: 产品编号:	HDGC2509HM-XP
				DATE	SCALE
				UNIT	CODE NUMBER
				2015-04-25	2.5:1 mm A008