

修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2014-12-02

SPECIFICATIONS:

Current Rating: 3A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -25°C ~ +85°C
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1500V AC/minute
Material: PBT,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	2.54	6.14	18P	43.18	46.78
3P	5.08	8.68	19P	45.72	49.32
4P	7.62	11.22	20P	48.26	51.86
5P	10.16	13.76	21P	50.80	54.40
6P	12.70	16.30	22P	53.34	56.94
7P	15.24	18.84	23P	55.88	59.48
8P	17.78	21.38	24P	58.42	62.02
9P	20.32	23.92	25P	60.96	64.56
10P	22.86	26.46	26P	63.50	67.10
11P	25.40	29.00	27P	66.04	69.64
12P	27.94	31.54	28P	68.58	72.18
13P	30.48	34.08	29P	71.12	74.72
14P	33.02	36.62	30P	73.66	77.26
15P	35.56	39.16	31P	76.20	79.80
16P	38.10	41.70	32P	78.74	82.34
17P	40.64	44.24			



深圳市华德共创科技有限公司

Shenzhen Huade co-create Technology Co.,LTD

TEL : 0755-27129737 FAX : 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表				TITLE: 产品名称: 2.54mm Pitch Housing	
X.X	±0.30	X.X°	±3°	APPD: 核准:	XIE
X.XX	±0.30	X.XX°	±2°	CHECK: 校对:	WANG
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图:	WANG
				PART NO: 产品编号:	HDGC2547HJ-XP
				DATE	SCALE
				UNIT	CODE NUMBER
				2014-12-02	3:1 mm A008