




修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2017-09-12







SPECIFICATIONS:

Current Rating: 3A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -25°C ~ +85°C
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1500V AC/minute
Pin Material: Brass/Gold over Nickel
Material: PBT,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	2.54	7.62	14P	33.02	38.10
3P	5.08	10.16	15P	35.56	40.64
4P	7.62	12.70	16P	38.10	43.18
5P	10.16	15.24	17P	40.64	45.72
6P	12.70	17.78	18P	43.18	48.26
7P	15.24	20.32	19P	45.72	50.80
8P	17.78	22.86	20P	48.26	53.34
9P	20.32	25.40	21P	50.80	55.88
10P	22.86	27.94	22P	53.34	58.42
11P	25.40	30.48	23P	55.88	60.96
12P	27.94	33.02	24P	58.42	63.50
13P	30.48	35.56	25P	60.96	66.04



深圳市华德共创科技有限公司

Shenzhen Huade co-create Technology Co.,LTD

TEL : 0755-27129737 FAX : 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表				TITLE: 产品名称: 2.54mm Pitch 90° Wafer	
X.X	±0.30	X.X°	±3°	APPD: 核准:	XIE
X.XX	±0.30	X.XX°	±2°	CHECK: 校对:	WANG
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图:	WANG
				PART NO: 产品编号:	HDGC2547WR-XP
				DATE	SCALE
				UNIT	CODE NUMBER
				2017-09-12	4:1 mm A008