

修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2015-07-12

Ordering Information:

HDGC3030WV-F-XP - *** - *** - ***
1 2 3 4

1.Part No.

2.Size(H):

(blank):2.00mm

H30:3.00mm

3.Material:

(blank):Nylon 66, UL94V-0

(blank):LCP, UL94V-0

GWT:LCP, UL94V-0,GWT 750°C

4.Finish:

(blank):Tin over Nickel

G:Gold over Nickel(1"U)

G3:Gold over Nickel(3"U)

G15:Gold over Nickel(15"U)

G30:Gold over Nickel(30"U)

SPECIFICATIONS:

Current Rating: 5A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range:-25°C ~ +85°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1500V AC/minute

Pin Material: Brass/Tin over Nickel

Material: Nylon 66,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2P	3.00	9.65	7.30	8P	21.00	27.65	25.30
3P	6.00	12.65	10.30	9P	24.00	30.65	28.30
4P	9.00	15.65	13.30	10P	27.00	33.65	31.30
5P	12.00	18.65	16.30	11P	30.00	36.65	34.30
6P	15.00	21.65	19.30	12P	33.00	39.65	37.30
7P	18.00	24.65	22.30				



深圳市华德共创科技有限公司

SHENZHEN HUADE CO-CREATE TECHNOLOGY CO.,LTD

TEL : 0755-27129737 FAX : 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表						TITLE: 3.00mm Pitch 产品名称: 180 ° Wafer			
X.X	±0.30	X.X°	±3°	APPD: 核准:	XIE	PART NO: HDGC3030WV-F-XP 产品编号:			
X.XX	±0.30	X.XX°	±2°	CHECK: 校对:	WANG	DATE	SCALE	UNIT	CODE NUMBER
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图:	WANG	2015-07-12	3:1	mm	A008