

修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2013-12-06

Ordering Information:
HDGC3961H-XP - * - **
1 2 3

1.Part No.

2.Style:

(blank) - Type 1


2 - Type 2

3 - Type 3

3.Material

(blank) - UL94V-2/Natural

V0 - UL94V-0/White



SPECIFICATIONS:

Current Rating: 7A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -25°C ~ +85°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1500V AC/minute

Material: Nylon 66,UL94V-2 or UL94V-0

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	3.96	8.43	14P	51.48	55.95
3P	7.92	12.39	15P	55.44	59.91
4P	11.88	16.35	16P	59.40	63.87
5P	15.84	20.31	17P	63.36	67.83
6P	19.80	24.27	18P	67.32	71.79
7P	23.76	28.23	19P	71.28	75.75
8P	27.72	32.19	20P	75.24	79.71
9P	31.68	36.15	21P	79.20	83.67
10P	35.64	40.11	22P	83.16	87.63
11P	39.60	44.07	23P	87.12	91.59
12P	43.56	48.03	24P	91.08	95.55
13P	47.52	51.99			



深圳市华德共创科技有限公司

SHENZHEN HUADE CO-CREATE TECHNOLOGY CO.,LTD

TEL : 0755-27129737 FAX : 0755-29940187

-TOLERANCES- OTHERWISE SPECIFIED 公差参数表					TITLE: 3.96mm Pitch 产品名称: Housing			
X.X	±0.30	X.X°	±3°	APPD: 核准: X I E	PART NO: HDGC3961H-XP 产品编号:			
X.XX	±0.30	X.XX°	±2°	CHECK: 校对: WANG	DATE	SCALE	UNIT	CODE NUMBER
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图: WANG	2013-12-06	2:1	mm	A008