

修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNA TURE	日期 DATE
A0		NEW RELEEASE	WANG	2015-05-22



Ordering Information:

HDGC4501HF-2xXP - **
1 2

1.Part No.
2.Material:
(blank):UL94V-0/White
V2:UL94V-2/Natural



SPECIFICATIONS:
Current Rating: 10A AC,DC
Voltage Rating: 300V AC,DC
Temperature Range:-25°C ~ +85°C
Contact Resistance: 7mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1500V AC/minute
Material: Nylon 66,UL94V-0(White)

Ordering Information & Dimensions

Circuits	Dimensions(mm)	
	A	B
2x2P	4.50	10.30
2x3P	9.00	14.80

Circuits	Dimensions(mm)	
	A	B
2x4P	13.50	19.30
2x6P	22.50	28.30

深圳市华德共创科技有限公司
SHENZHEN HUADE CO-CREATE TECHNOLOGY CO.,LTD
TEL：0755-27129737 FAX：0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表				APPD: 核准： XIE	TITLE: 产品名称： 4.50mm Pitch Housing			
X.X	±0.30	X.X°	±3°		PART NO: 产品编号： HDGC4501HF-2xXP			
X.XX	±0.30	X.XX°	±2°	CHECK: 校对： WANG	DATE	SCALE	UNIT	CODE NUMBER
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图： WANG	2015-05-22	1.5:1	mm	A008