



修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0		NEW RELEASE	WANG	2019-08-07



Ordering Information:
HDGC5030HFD-XP - $\frac{**}{2}$ - $\frac{**}{3}$

- Part No.
- Material:
(blank):Nylon 66,UL94V-0
GWT:Nylon 66,UL94V-0,GWT 750°C
- Color:
(blank):White
BK:Black
RD:Red
BL:Blue
YL:Yellow

SPECIFICATIONS:
Current Rating:10A AC,DC
Voltage Rating:300V AC,DC
Temperature Range: -25°C ~ +85°C
Contact Resistance: 10mΩ Max.
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1500V AC/minute
Material: Nylon 66,UL94V-0(White)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2x1P	5.00	6.20	2x6P	25.00	31.20
2x2P		11.20	2x8P	35.00	41.20
2x4P	15.00	21.20			



深圳市华德共创科技有限公司

SHENZHEN HUADE CO-CREATE TECHNOLOGY CO.,LTD

TEL : 0755-27129737 FAX : 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表					TITLE: 5.00mm Pitch 产品名称: Housing			
X.X	±0.30	X.X° ±3°	APPD: 核准:	XIE	PART NO: 产品编号: HDGC5030HFD-2xXP			
X.XX	±0.30	X.XX° ±2°	CHECK: 校对:	WANG	DATE	SCALE	UNIT	CODE NUMBE
X.XXX	±0.10	X.XXX° ±1°	DRAW: 绘图:	WANG	2019-08-07	2:1	mm	A008

