

修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNA TURE	日期 DATE
A0		NEW RELEEASE	WANG	2015-04-12





Ordering Information:

HDGC6203HMA-XP - * - **
1 2 3

1.Part No.
2.Material:
(blank):UL94V-2
V0:UL94V-0
3.Color:
(blank):Natural
WH:White
BK:Black

SPECIFICATIONS:
Current Rating: 10A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -25°C ~ +85°C
Contact Resistance: 10mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1500V AC/minute
Material: Nylon 66,UL94V-2(Natural)

Ordering Information & Dimensions

Circuits	Dimensions(mm)	
	A	B
2P	6.20	13.20
3P	12.40	19.40

Circuits	Dimensions(mm)	
	A	B
4P	18.60	25.60

深圳市华德共创科技有限公司
SHENZHEN HUADE CO-CREATE TECHNOLOGY CO.,LTD
TEL：0755-27129737 FAX：0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表								
X.X	±0.30	X.X°	±3°	APPD: 核准：	XIE	TITLE: 产品名称：	6.20mm Pitch Housing	
X.XX	±0.30	X.XX°	±2°	CHECK: 校对：	WANG	PART NO: 产品编号：	HDGC6203HMA-XP	
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图：	WANG	DATE	SCALE	UNIT / CODE NUMBER
						2015-04-12	2.5:1	mm / A008