





Specifications

Current rating: 1A AC, DC
 Voltage rating: 125V AC, DC
 Temperature range: -25°C ~ +85°C
 Contact resistance: 20mΩ Max.
 Insulation resistance: 100MΩ Min.
 Withstanding voltage: 500V AC/minute
 Compliant with RoHS and REACH
 Meet the HF/Halogen Free, need to customize
 Contact HDGC for details



Assembly layout






HDGC1254 Series 1.25mm (.049") Pitch Wire to Board Connector

HDGC1254-T

1.25mm pitch Crimp Terminal

Reference Informations:

*Used in HDGC1254H-XP series Housing



Ordering information & Specifications:

Unit:mm

Part NO.	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
HDGC1254-TP	AWG#28-#32	0.90mm(max)	Phosphor Bronze	Tin over Nickel	20,000 PCS
HDGC1254-GP	AWG#28-#32	0.90mm(max)	Phosphor Bronze	Gold over Nickel	20,000 PCS

Optional Gold plating available but MOQ requested

HDGC1254H-XP

1.25mm pitch Housing


Reference Informations:

*Material:Nylon 66,UL94V-0

*Suitable HDGC1254-T series Terminal

*Mates with HDGC1254WR-S-XP series Wafer

*Color:White



Ordering Information:



HDGC1254H-XP - ***
1 2

1.Part No.

2.Material:

(Blank):Nylon 66,UL94V-0

GWT :Nylon 66,UL94V-0 GWT 750℃



Ordering Information & Dimensions:

PART NO.	Dimensions			PART NO.	Dimensions		
	A	B	C		A	B	C
2P	1.25	2.72	5.72	17P	20.00	21.47	24.47
3P	2.50	3.97	6.97	18P	21.25	22.72	25.72
4P	3.75	5.22	8.22	19P	22.50	23.97	26.97
5P	5.00	6.47	9.47	20P	23.75	25.22	28.22
6P	6.25	7.72	10.72	21P	25.00	26.47	29.47
7P	7.50	8.97	11.97	22P	26.25	27.72	30.72
8P	8.75	10.22	13.22	23P	27.50	28.97	31.97
9P	10.00	11.47	14.47	24P	28.75	30.22	33.22
10P	11.25	12.72	15.72	25P	30.00	31.47	34.47
11P	12.50	13.97	16.97	26P	31.25	32.72	35.72
12P	13.75	15.22	18.22	27P	32.50	33.97	36.97
13P	15.00	16.47	19.47	28P	33.75	35.22	38.22
14P	16.25	17.72	20.72	29P	35.00	36.47	39.47
15P	17.50	18.97	21.97	30P	36.25	37.72	40.72
16P	18.75	20.22	23.22				

Unit: mm



HDGC1254 Series 1.25mm (.049") Pitch Wire to Board Connector

HDGC1254HA-XP

1.25mm pitch Housing

Reference Informations:

*Material: Nylon 66, UL94V-0

*Suitable HDGC1254-T series Terminal

*Color: White

Ordering Information:






HDGC1254HA-XP - ***
1 2

1. Part No.


2. Material:

(Blank): Nylon 66, UL94V-0

GWT : Nylon 66, UL94V-0 GWT 750 °C



HDGC1254HA-4P



HDGC1254HA-6P

Unit: mm

HDGC1254WR-S-XP

1.25mm pitch 90° Wafer-SMT TYPE

Reference Informations:

*Material: Pin: Brass/Tin over Nickel on solder area


Gold over Nickel on contact area

Solder Tabs: Brass/Tin over Nickel


Insulator: Nylon 6T, UL94V-0

*Mates with HDGC1254H-XP series Housing

*Color: Beige



P.C.B. LAYOUT



Ordering Information:



HDGC1254WR-S-XP - ***
1 2

1. Part No.

2. Material:

(Blank): Nylon 6T, UL94V-0

GWT : Nylon 6T, UL94V-0 GWT 750 °C



Circuit 1

Ordering Information & Dimensions:

PART NO.	Dimensions		PART NO.	Dimensions	
	A	B		A	B
2P	1.25	7.65	17P	20.00	26.40
3P	2.50	8.90	18P	21.25	27.65
4P	3.75	10.15	19P	22.50	28.90
5P	5.00	11.40	20P	23.75	30.15
6P	6.25	12.65	21P	25.00	31.40
7P	7.50	13.90	22P	26.25	32.65
8P	8.75	15.15	23P	27.50	33.90
9P	10.00	16.40	24P	28.75	35.15
10P	11.25	17.65	25P	30.00	36.40
11P	12.50	18.90	26P	31.25	37.65
12P	13.75	20.15	27P	32.50	38.90
13P	15.00	21.40	28P	33.75	40.15
14P	16.25	22.65	29P	35.00	41.40
15P	17.50	23.90	30P	36.25	42.65
16P	18.75	25.15			

Unit: mm